

www.sealsdirect.co.uk

## **MATERIAL DATA SHEET**

DESCRIPTION PORTHOLE RUBBER STRIP 38MM X 3MM



ORDER CODE

Issue date: 25.04.18

**PHR 141** 

PARAMETER	VALUE
MATERIAL	WHITE NATURAL RUBBER
DIMENSIONAL TOLERANCE – WIDTH – THICKNESS	±0.3mm ±0.4mm
DENSITY	1.02G/CM <sup>3</sup>
HARDNESS	35 – 45° SHORE A
TEMPERATURE RANGE	-20°C TO +70°C
TENSILE STRENGTH	16MPa (MIN)
ELONGATION @ BREAK	600%
ABRASION RESISTANCE	120mm <sup>3</sup>
TEAR RESISTANCE	15KG/CM

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1

Seals + Direct Ltd

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH Tel: 01425 617722 Fax: 01425 610967 E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100