

MATERIAL DATA SHEET

DESCRIPTION

**LIGHT BLUE TREADMASTER ANTI-SLIP
DECK COVERING (DIAMOND PATTERN)**



ORDER CODE

TM 229

PARAMETER	VALUE
MATERIAL	LIGHT BLUE NITRILE/PVC
DENSITY (ISO 2781)	1.04G/CM ³
TENSILE STRENGTH (ASTM F152)	3MPA
ELONGATION @ BREAK (ASTM F152)	65%
ABRASION RESISTANCE (TABER, 500G, 3000CYC, H22 WHEELS)	1G, 0.3MM LOSS
DRY SKID RESISTANCE (BRR PENDULUM)	78
WET SKID RESISTANCE (BRR PENDULUM)	45
SHEET SIZE	1.2M X 0.9M X 3MM THICK

GENERAL CHARACTERISTICS

IT IS UNAFFECTED BY EXPOSURE TO SEA WATER AND ALSO RESISTS THE CHEMICAL EFFECTS OF OIL, FUEL AND OTHER COMMONLY USED SUBSTANCES, HOWEVER ANY SPILLAGES SHOULD BE CLEANED UP PROMPTLY TO AVOID SURFACE STAINING.

CLEANING FLUIDS CONTAINING BLEACH, AND ABRASIVE CLEANERS, MUST NEVER BE USED.

BEING A SUBSTANTIALLY NATURAL PRODUCT, SOME COLOURS MAY SHOW A DEGREE OF FADING AFTER A PERIOD OF EXPOSURE TO THE ELEMENTS.

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.