


www.sealsdirect.co.uk

MATERIAL DATA SHEET

DESCRIPTION RIBBED RUBBER MATTING 10M LONG X 1.0M WIDE X 3MM THK



ORDER CODE

Issue date: 06.03.17

M 620

PARAMETER	VALUE
MATERIAL	BLACK NR / SBR
SPECIFIC GRAVITY	1.5
HARDNESS	65 – 75° SHORE A
TENSILE STRENGTH	2.5MPA
ELONGATION @ BREAK	130% (MIN)
ABRASION RESISTANCE	300 MM ³
TEMPERATURE RANGE	-20°C TO +70°C
GENERAL CHARACTERISTICS	
GENERAL PURPOSE MATTING FOR PROTECTING FLOORS	

• ANTI-SLIP FINISH

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1

Seals + Direct Ltd

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH Tel: 01425 617722 Fax: 01425 610967 E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100