

MATERIAL DATA SHEET

DESCRIPTION

CARAVAN DOOR SEAL WITH SPONGE BULB

**ORDER CODE**

CS 6538

PARAMETER	VALUE
BASE MATERIAL	BLACK EPDM
HARDNESS	70° SHORE A
SPECIFIC GRAVITY	1.3
TENSILE STRENGTH	8MPA
ELONGATION @ BREAK	525%
TEMPERATURE RANGE	-40°C TO +120°C
<u>AGED 70 HOURS @ 70°C</u>	
HARDNESS CHANGE	+2%
TENSILE STRENGTH CHANGE	+7%
ELONGATION @ BREAK CHANGE	-15%
SPONGE MATERIAL	BLACK EPDM SPONGE
SPECIFIC GRAVITY	0.7
TENSILE STRENGTH	3MPA
ELONGATION @ BREAK	360%
OZONE RESISTANCE	PASS
UV RESISTANCE	PASS

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1

Issue date: 28.11.25

Seals + Direct Ltd

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH

Tel: 01425 617722 **Fax:** 01425 610967 **E-mail:** sales@sealsplusdirect.co.uk

Reg. No 4989100