


www.sealsdirect.co.uk

MATERIAL DATA SHEET

DESCRIPTION

BRONZE TIMBER FOAM FLIPPER SEAL 50M COIL



ORDER CODE

TFS 3249

PARAMETER	VALUE
MATERIAL	POLYPROPYLENE BASE INSERT WITH POLYURETHANE FOAM INNER CORE COVERED WITH POLYETHYLENE OUTER SKIN
WORKING DISTANCE RANGE (BS EN12365)	>8MM ≤10MM
LINEAR COMPRESSION FORCE (BS EN12365-2)	>20N/M ≤50N/M
WORKING TEMPERATURE RANGE (BS EN12365)	-20°C TO +85°C
DEFLECTION RECOVERY (BS EN12365-3)	>80% TO 90%
RECOVERY AFTER AGEING (BS EN12365-4)	>30% TO 40%
GENERAL CHARACTERISTICS	
 EXCELLENT INSULATION PROPERTIES GOOD ACOUSTIC PROPERTIES UV STABLE NON TOXIC MOULD AND MILDEW RESISTANT LOW FRICTION AND HIGH RESISTANCE TO ABRASION, OZONE AND BIOLOGICAL ATTACK RESISTANT TO MOST PAINTS AND VARNISHES 	

• 10 YEAR LIFE CYCLE

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1

Issue date: 20.12.18

Seals + Direct Ltd

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH Tel: 01425 617722 Fax: 01425 610967 E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100