

MATERIAL SAFETY DATA SHEET

DESCRIPTION BLACK POLYURETHANE ADHESIVE 310ML



ORDER CODE
S 136 MSDS

SECTION 1: Identification of the substance / preparation and company

1.1 Product identifier

S136

1.2 Relevant identified uses of the substance or mixture and uses advised against

Adhesives Sealants

1.3 Details of the supplier of the safety data sheet:

Seals + Direct LTD
Unit 6, Milton Business Centre
Wick Drive, New Milton
Hants, BH25 6RH

Tel: 01425 617722 Fax: 01425 610967

Email: sales@sealsplusdirect.co.uk

1.4 Emergency telephone number

Tel: 01425 617722 (Mon – Fri 8:30am – 5pm)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 14 Issue date: 06.03.17

Seals + Direct Ltd



The product is classified and labelled according to the CLP regulation.

Hazard pictograms



Signal word

Danger

Hazard-determining components of labelling

methylenediphenyl diisocyanate, isomeres and homologues

Hazard statements

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements

P261 Avoid breathing mist/vapours/spray.

P280 Wear protective gloves.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Additional information

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition / information on ingredients

3.2 Chemical characterisation

Mixtures

Description

Mixture of several substances



www.sealsdirect.co.uk

S 136 MSDS CONTINUED

Dangerous components				
CAS: 1330-20-7	xylene, mixed isomers, pure <			
EINECS: 215-535-7	Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1,			
Reg.nr.: 01-2119488216-32-xxxx	H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit.			
	2, H315; Eye Irrit. 2, H319; STOT SE 3, H335			
CAS: 90622-57-4	hydrocarbons, C11-C12	< 2.0%		
EC number: 918-167-1	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic			
Reg.nr.: 01-2119472146-39-xxxx	4, H413			
CAS: 28553-12-0	di-"isononyl" phthalate	< 2.0%		
EINECS: 249-079-5	substance with a workplace exposure limit			
Reg.nr.: 01-2119430798-28-xxxx				
CAS: 101-68-8	diphenylmethane-4,4'-diisocyanate	< 0.5%		
EINECS: 202-966-0	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;			
Reg.nr.: 01-2119457014-47-xxxx	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;			
	Skin Sens. 1, H317; STOT SE 3, H335			
CAS: 25686-28-6	4,4'-methylenediphenyl diisocyanate, oligomers	< 0.2%		
NLP: 500-040-3	Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373;			
Reg.nr.: 01-2119457013-49-xxxx	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319;			
	Skin Sens. 1, H317; STOT SE 3, H335			

SVHC

Doesn't contain SVHC-substances

Additional information

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

After inhalation

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness bring patient into a stable side position for transport.

After skin contact

Treat affected skin with cotton wool or cellulose. Then wash and rinse thoroughly with water and a mild cleaning agent.

After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Do not induce vomiting; call for medical help immediately.



4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing media

Suitable extinguishing agents
Water spray
Alcohol-resistant foam
Fire-extinguishing powder
Carbon dioxide

For safety reasons unsuitable extinguishing agents Water with full jet.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

6.2 Environmental precautions

Do not allow to enter sewers / surface or ground water.

6.3 Methods and material for containment and cleaning up

Pick up mechanically.

6.4 Reference to other sections

Page 4 of 14 Issue date: 06.03.17



See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Information about protection against explosions and fires

The product contains small quantities of organic solvents. The possibility of an ignitable vapour / air mixture forming is very slight but, under certain local conditions, this should not be overlooked. Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage requirements to be met by storerooms and receptacles Prevent any seepage into the ground.

<u>Information about storage in one common storage facility</u> Store away from foodstuffs.

Further information about storage conditions

Protect from frost.

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in dry conditions.

Storage class (according german VCI-concept)

13

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure Controls / Personal Protection

Additional information about design of technical systems

No further data; see item 7.

Page 5 of 14 Issue date: 06.03.17



8.1 Control parameters

Additional information about design of technical systems No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace				
28553-12-0 di-"isononyl" phthalate				
WEL (Great Britain)	Long-term value: 5 mg/m ³			
101-68-8 diphenylmethane-4,4'-diisocyanate				
WEL (Great Britain)	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO			
25686-28-6 4,4'-methylenediphenyl diisocyanate, oligomers				
WEL (Great Britain)	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO			
Ingredients with biological limit values				
1330-20-7 xylene, mixed isomers, pure				
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid			

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

The usual precautionary measures should be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of the work.

Immediately remove all soiled and contaminated clothing.

Breathing equipment

Not required with good ventilation and/or adequate extractor facilities.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Short term filter device A2 (DIN EN 14387 / DIN EN 141)

Page 6 of 14 Issue date: 06.03.17



www.sealsdirect.co.uk

S 136 MSDS CONTINUED

Protection of hands

Direct contact with the chemical preparation must be avoided by organizational measures. Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

Compliance with the stated penetration time (starts with the first product contact) must be ensured!

The gloves need to be disposed of after the penetration time and new gloves used!

For the permanent contact gloves made of the following materials are suitable If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the "Barrier 02-100" underglove from Ansell (penetration time 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable

Fluorinated rubber (Viton) (0.7mm - penetration time 15 min)

As protection from splashes gloves made of the following materials are suitable Recommended for protection from splashes: disposable nitrile gloves (minimum thickness 0.12 mm) with long cuffs. After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

Eye protection

Safety glasses

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance

Form Pasty

Penetrometer test according ADR 2.3.4.3

Test result: solid (penetration after 5s < 15mm)

Colour Black

Odour Solvent-like

Change in condition

Boiling point/Boiling range Not applicable

Flash point Not applicable

Ignition temperature > 200 °C

Explosion limits Lower: 0.4 Vol %

Page 7 of 14 Issue date: 06.03.17

Seals + Direct Ltd

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH

Tel: 01425 617722 Fax: 01425 610967 E-mail: sales@sealsplusdirect.co.uk

Reg. No 4989100



Upper: 7.6 Vol %

Vapour pressure at 20 °C < 100 hPa

Specific gravity at 20 °C 1.17 g/cm³

Solubility in / Miscibility Insoluble

with water reacts with water

Solvent content

Organic solvents 5.9 % VOC (EU) 68.9 g/l VOC (EU) 5.90 % VOC (CH) 5.90 %

9.2 Other information

Burning test according 33.2.1.4 "Manual of Test and Criteria" [Recommendations on the TRANSPORT OF DANGEROUS GOODS (United Nations)]

Burning rate: 2,2mm/s [Not a dangerous good according class 4.1(ADR)]

SECTION 10: Stability and Reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided. No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with alcohols, amines, aqueous acids and alkalis.

Reacts with water forming carbon dioxide. In closed containers there is a danger of bursting, due to build up of pressure.

10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials

Page 8 of 14 Issue date: 06.03.17



No further relevant information available.

10.6 Hazardous decomposition products

In case of fire, the following substance(s) may occur: Hydrogen chloride (HCl) Nitrogen oxides Sulphur oxides (SOx)

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification				
ATE (Acute Toxicity Estimates)				
Dermal	LD50	29891 mg/kg		
Inhalative	LD50/4 h	299 mg/l		

1 330-20-7 xylene, mixed isomers, pure			
Oral	LD50	3523 mg/kg (rat)	
Dermal	LD50	1100 mg/kg (ATÉ)	
Inhalative	LC50/4 h	11 mg/l (ATE)	

Primary irritant effect

Skin corrosion/irritation

Prolonged or repeated contact with the skin may cause skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity

Based on available data, the classification criteria are not met.



Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological Information

12.1 Toxicity

Aquatic toxicity

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Additional ecological information

General notes

Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT Not applicable. vPvB Not applicable.

Page 10 of 14 Issue date: 06.03.17



12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal Consideration

13.1 Waste treatment methods

Recommendation

Disposal in accordance with official regulations

EWC-Code(s)

To be treated as industrial waste: do not dispose of in or on soil, in watercourses or bodies, or through a sewage system. These EU refuse code numbers are recommendations for waste accruing through the use of adhesives and sealants. Any waste produced from organic solvents or other dangerous substances listed under item 3 of this safety datasheet is itself classified as dangerous (*).

Waste accruing during application

080409* waste adhesives and sealants containing organic solvents or other dangerous substances

080410 waste adhesives and sealants other than those mentioned in 080409

Waste accruing during cleaning

08 04 11* adhesive and sealant sludges containing organic solvents or other dangerous substances

08 04 12 adhesive and sealant sludges other than those mentioned in 080411

Soiled waste packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances.

Clean waste packaging

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

Uncleaned packagings

Recommendation

Disposal must be made according to official regulations.



www.sealsdirect.co.uk

S 136 MSDS CONTINUED

SECTION 14: Transport Information

14.1 UN-Number

ADR,RID,ADN, ADN, IMDG, IATA Void

14.2 UN proper shipping name

- ADR,RID,ADN, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

- ADR, RID, ADN, IMDG, IATA

- Class Void

14.4 Packing group

ADR, RID, ADN, IMDG, IATA Void

14.5 Environmental hazards

Marine pollutant No

14.6 Special precautions for userNot applicable

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

Transport/Additional information Protect from moisture

UN "Model Regulation" Void

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3, 20, 52a, 56a

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

Page 12 of 14 Issue date: 06.03.17



SECTION 16: Other Information

Revision date Refer to the date at bottom of sheet

For industrial use only.

Legend of H- and R-phrases, concerning the in chapter 3 mentioned substances (marking of product please see chapter 2)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H413 May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweis (Swiss

Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

Page 13 of 14 Issue date: 06.03.17



SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4