SEALS+DIRECT FIRE RETARDANT EXTRUSION SILICONE RUBBER 30 SHORE A (AEROSPACE SPEC)

CMDS0019

DOCUMENT NO.



COMPOUND MATERIAL DATA SHEET

GENERAL OVERVIEW:

A fire-retardant compound with good mechanical properties. This compound has good heat stability inside a wide temperature range. Pigmentation options are limited due to off-white base colour.

FEATURES:

• CS 25.853(a) Amdt.21 App.F Pt.I(a)(1)(iv) & (b)(5) 15s. Horiz. - Pass 31/07/18

- CS 25.853(a) Amdt.21 App.F Pt.I(a)(1)(v) & (b)(5) 15s. Horiz. Pass 20/10/22
- Smoke Emission* ABD0031 IssF Pass 31/07/18
- Toxic Gas Emission (ppm) ABD0031 IssF Pass 31/07/18

PROPERTIES:

PARAMETER	TEST METHOD	TYPICAL VALUE			
Temperature Range		-50°C to +220°C			
Density at 20°C	ISO 1183-1 A	1.13g/cm³ (Approx)			
Hardness Shore A	DIN 53505	30°			
Tensile Strength	DIN 53504 S1 / ISO 37	9.3N/mm²			
Elongation at Break	DIN 53504 S1	616%			
Tear Strength	ASTM D 624 B	15.2N/mm			
Compression Set (22h / 175°C)	DIN ISO815-B	33%			

NOTES:

Cure conditions: 1.5% (50% paste of bis (2,4-dichlorobenzoyl)-peroxide in silicone fluid), 10 min / 135°C in press, post-cured 4h / 200°C.

ISSUE	DATE	ISSUE	DATE	I	ISSUE	DATE	ISSUE	DATE	ISSUE	DATE	ISSUE	DATE	ISSUE	I	DATE
1	16.01.25														
CR	APPROVED	CR	APPROVI	ED (CR	APPROVED	CR	APPROVED	CR	APPROVED	CR	APPROVED	CR	,	APPROVED
	PJH														
Seals+Direct Ltd					This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also ORIGINATOR										ATOR
Unit 6, Milton Business Centre, Wick Drive New Milton, Hants, BH25 6RH, UK Tel: 01425 617722 Web: sealsdirect.co.uk				applie	applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained with our CHARTED DATE									CJM	
				produ										D DATE	
E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100 this data sheet is subject to change without notice.											16/01/25				
S+D/MDS003/Compound Material Data Sheet/Ver 1.															