

DESCRIPTION

FIRE RETARDANT EXTRUSION SILICONE RUBBER 60 SHORE A (AEROSPACE SPEC)

DOCUMENT NO.

CMDS0022



COMPOUND MATERIAL DATA SHEET

GENERAL OVERVIEW:

A fire-retardant compound with good mechanical properties. This compound has good heat stability inside a wide temperature range. Pigmentation options are limited due to off-white base colour.

FEATURES:

- CS 25.853(a) Amdt.21 App.F Pt.I(a)(1)(i) & (b)(4) 60s. Vert. Pass 13/12/22
- CS 25.853(a) Amdt.21 App.F Pt.I(a)(1)(v) & (b)(5) 15s. Horiz. Pass 20/10/22
- CS 25.855(d) Amdt.21 App.F Pt.I(a)(2)(ii) & (b)(6) 30s. 45° Pass 11/10/16
- Smoke Emission* ABD0031 IssF Pass 20/12/22
- Toxic Gas Emission (ppm) ABD0031 IssF Pass 20/12/22

PROPERTIES:

PARAMETER	TEST METHOD	TYPICAL VALUE			
Temperature Range		-50°C to +220°C			
Density at 20°C	ISO 1183-1 A	1.18g/cm³ (Approx) 60° 11N/mm²			
Hardness Shore A	DIN 53505				
Tensile Strength	DIN 53504 S1 / ISO 37				
Elongation at Break	DIN 53504 S1	460%			
Tear Strength	ASTM D 624 B	21N/mm			
Compression Set (22h / 175°C)	DIN ISO815-B	32%			

NOTES:

Cure conditions: 1.5% (50% paste of bis (2,4-dichlorobenzoyl)-peroxide in silicone fluid), $10 \text{ min} / 135^{\circ}\text{C}$ in press, post-cured $4\text{h} / 200^{\circ}\text{C}$.

	ISSUE	DATE												
	1	16.01.25												
	CR	APPROVED												
ſ		P.IH												

Seals+Direct Ltd

Unit 6, Milton Business Centre, Wick Drive New Milton, Hants, BH25 6RH, UK Tel: 01425 617722 Web: sealsdirect.co.uk mail: sales@sealsplusdirect.co.uk Reg. No 4989101 This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

© SEALS + DIRECT LTD

ORIGINATOR

CJM

CREATED DATE

16/01/25