

www.sealsdirect.co.uk

## **MATERIAL DATA SHEET**

HEAVY DUTY RUBBER FLOOR MAT 1.828M LONG X 1.22M WIDE X 17MM THK



ORDER CODE

M 243

PARAMETER	VALUE
MATERIAL	BLACK NR / SBR
SPECIFIC GRAVITY	1.6
HARDNESS	65° SHORE A
TENSILE STRENGTH	2.5MPA
ELONGATION @ BREAK	200% (MIN)
ABRASION RESISTANCE	250 MM <sup>3</sup>
TEMPERATURE RANGE	-20°C TO +70°C
GENERAL CHARACTERISTICS	
SUITABLE FOR INDUSTRIAL AREAS, HORSE STABLES, DOG KENNELS	

- AND RUNS AND WEIGHT LIFTING AREAS ETC
- STUDDED SURFACE FOR GRIP
- CUSHIONING UNDERFOOT REDUCES STRAIN
- PROVIDES ADDITIONAL WARMTH AND INSULATION
- GROOVED UNDERSIDE FOR EFFECTIVE DRAINAGE

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1

Issue date: 06.03.17

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH Tel: 01425 617722 Fax: 01425 610967 E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100

Seals + Direct Ltd