


MATERIAL DATA SHEET

DESCRIPTION

**NOISE INSULATION MATERIAL
1.2M LONG X 0.6M WIDE X 24MM THICK**



ORDER CODE

NI 617

PARAMETER	VALUE
MATERIAL	LEAD SHEET SANDWICHED BETWEEN 2 LAYERS OF FIRE RESISTANT FOAM COVERED WITH BRIGHT FOIL
<u>ACOUSTIC PERFORMANCE</u>	
125HZ	12DB
250HZ	14DB
500HZ	16DB
1000HZ	24DB
2000HZ	26DB
4000HZ	33DB
<u>GENERAL CHARACTERISTICS</u>	
<ul style="list-style-type: none">A CLASS '0' FLEXIBLE COMPOSITE COMPRISING OF AN ACOUSTIC LEAD SHEET SANDWICHED BETWEEN TWO LAYERS OF FIRE RESISTANT FOAM, WITH A BRIGHT CLASS '0' REINFORCED FOIL FACING TO ONE SIDE.FIRE RATING: BUILDING REGULATIONS 1976 SECTION E15: CLASS '0' BS476 PART 6 INDEX 1 10.3 SUB-INDEX 1 5.3 BS476 PART 7 CLASS '1'	

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.