



## MATERIAL DATA SHEET

PARAMETER	VALUE
MATERIAL	BLACK EPDM
HARDNESS	66 – 74° SHORE A
SPECIFIC GRAVITY	1.22
TENSILE STRENGTH	10.5MPA
ELONGATION @ BREAK	200%
TEAR RESISTANCE	11KN/M
COMPRESSION SET (22 HOURS @ 70°)	25% (MAX)
TEMPERATURE RANGE	-35°C TO +100°C

ISSUE 2	DATE 21.08.24	ISSUE	DATE	ISSUE	DATE	ISSUE	DATE	ISSUE	DATE	ISSUE	DATE	ISSUE	DATE
CR CR0002	APPROVED PJH	CR	APPROVED	CR	APPROVED	CR	APPROVED	CR	APPROVED	CR	APPROVED	CR	APPROVED
<b>Seals+Direct Ltd</b> Unit 6, Milton Business Centre, Wick Drive New Milton, Hants, BH25 6RH, UK Tel: 01425 617722 Web: sealsdirect.co.uk E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100		This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.										ORIGINATOR  CREATED DATE 21/08/24	