



MATERIAL DATA SHEET

| PARAMETER | VALUE |
|-------------------------------------|--|
| SPONGE MATERIAL | EXPANDED EPDM SKINNED CLOSED CELL SPONGE |
| DENSITY RANGE | 0.5 – 0.9 G/CM ³ |
| WATER ABSORPTION | 5% MAX |
| COMPRESSION SET (22 HOURS @ R/T) | 50% |
| COMPRESSION SET (24 HOURS RECOVERY) | 25% MAX |
| OZONE RESISTANCE | EXCELLENT |
| WEATHER RESISTANCE | EXCELLENT |
| UV LIGHT RESISTANCE | EXCELLENT |
| MOULD GROWTH RESISTANCE | VERY GOOD |
| OIL RESISTANCE | NO |
| LOW TEMPERATURE FLEXIBILITY | PASS |
| OVEN AGEING (7 DAYS @ 70°C) | ±30% |

| | | | | | | | | | | | | | |
|------------|------------------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|
| ISSUE 2 | DATE 08.01.25 | ISSUE | DATE | ISSUE | DATE | ISSUE | DATE | ISSUE | DATE | ISSUE | DATE | ISSUE | DATE |
| CR 0007 | APPROVED PJH | CR | APPROVED | CR | APPROVED | CR | APPROVED | CR | APPROVED | CR | APPROVED | CR | APPROVED |

Seals+Direct Ltd
Unit 6, Milton Business Centre, Wick Drive
New Milton, Hants, BH25 6RH, UK
Tel: 01425 617722 Web: sealsdirect.co.uk
E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

© SEALS + DIRECT LTD

ORIGINATOR

CREATED DATE

08/01/25