


www.sealsdirect.co.uk

## **MATERIAL DATA SHEET**

DESCRIPTION BLACK PVC U FENDER

TO FIT A 9MM EDGE – 15 METRE LENGTH



ORDER CODE

Issue date: 16.02.17

**PFU 559** 

PARAMETER	VALUE
MATERIAL	BLACK PVC
DENSITY (BS2782 620A)	1.24G/CM <sup>3</sup>
HARDNESS	67° SHORE A
BSS SOFTNESS NUMBER (BS2782 365A)	58
TENSILE STRENGTH (BS2782 320A)	18.4MN/M <sup>2</sup>
ELONGATION @ BREAK (BS2782 320A)	390%
100% MODULUS (BS2782 320A)	7.58MN/M <sup>2</sup>
COLD FLEX TEMPERATURE (BS2782 150B)	-26°C
TEMPERATURE RANGE	-20°C TO +60°C

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1

Seals + Direct Ltd

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH Tel: 01425 617722 Fax: 01425 610967 E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100