


www.sealsdirect.co.uk

MATERIAL DATA SHEET

DESCRIPTION

BLACK FLIPPER GASKET TO FIT A 4MM WIDE SLOT



ORDER CODE

Issue date: 06.12.16

WS 2271

PARAMETER	VALUE
MATERIAL	TPS/TPO
HARDNESS (ISO 868)	62° SHORE A
DENSITY (ISO 2781)	1.09G/CM ³
TENSILE STRENGTH (ISO 37)	5.5MPA
ELONGATION @ BREAK (ISO 37)	700%
COMPRESSION SET (ISO 815 TYPE B) 24 HOURS @ 23°C 24 HOURS @ 70°C	20% 50%
TEAR STRENGTH (ISO 34 METHOD C)	25N/MM
TEMPERATURE RANGE	-50°C TO +75°C
GENERAL PROPERTIES	
WEATHER RESISTANCE	EXCELLENT
CHEMICAL RESISTANCE	MODERATE (EXCLUDING ORGANIC SOLVENTS, AROMATIC AND VEGETABLE OIL)
RECYCLABILITY	100%

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1

Seals + Direct Ltd

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH Tel: 01425 617722 Fax: 01425 610967 E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100