

www.sealsdirect.co.uk

MATERIAL DATA SHEET

DESCRIPTION

WHITE EASY FIT D FENDER TRACK



ORDER CODE

Issue date: 12.10.17

PFDBT 4046

PARAMETER	VALUE
MATERIAL	PVC
HARDNESS	100° SHORE A
SPECIFIC GRAVITY (ASTM D792 1986 METHOD A)	1.51
TENSILE STRENGTH (BS 2782 METHOD 320C 1976)	39MPA
SOFTENING POINT (VICAT) (BS 2782 METHOD 120B (B50): 1990	79°C
TEMPERATURE RANGE	-10°C TO +60°C
GENERAL CHARACTERISITCS	
 UV STABILISED PHTHALATE FREE 100% RECYCLABLE 	

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1

Seals + Direct Ltd

Unit 6, Milton Business Centre, Wick Drive, New Milton, Hants, BH25 6RH Tel: 01425 617722 Fax: 01425 610967 E-mail: sales@sealsplusdirect.co.uk Reg. No 4989100