


MATERIAL DATA SHEET

DESCRIPTION

**NON SETTING BUTYL GLAZING TAPE
25MM WIDE X 3MM THICK X 15M ROLL**



ORDER CODE

S 3287

PARAMETER	VALUE
MATERIAL	WHITE BUTYL TAPE WITH SILICONISED RELEASE PAPER
DYNAMIC TENSILE ADHESION (H5)	25N/CM ²
DYNAMIC SHEAR ADHESION (H15)	20N/CM ²
90° PEEL ADHESION (H48)	12N/CM
180° PEEL ADHESION (H41)	24N/CM
DENSITY (H6)	1.5G/CM ³
MOISTURE VAPOUR TRANSMISSION RATE (ISO9932 / BS ISO 15106)	0.13G/M ² /24HE/MM
TEMPERATURE RANGE	-40°C TO +90°C

GENERAL CHARACTERISTICS

- EXCELLENT ADHESION TO A WIDE RANGE OF SUBSTRATES
- GOOD UV RESISTANCE
- REMAINS FLEXIBLE THROUGHOUT ITS SERVICE LIFE
- APPROVED BY NATIONAL FEDERATION OF ROOFING CONTRACTORS (NFRC) CLASS A PERFORMANCE – THIRD PARTY CERTIFICATION BY A UKAS ACCREDITED LABORATORY
- SHELF LIFE: 24 MONTHS WHEN STORED FLAT IN ORIGINAL PACKAGING IN COOL, DRY CONDITIONS

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.