

www.sealsdirect.co.uk

MATERIAL DATA SHEET

DESCRIPTION

ADHESIVE SCRIM TAPE 25MM WIDE 10M LONG



ORDER CODE

SAT 3167

General Description

SAT3167 is a high tack modified acrylic scrim tape. The high performance adhesive is supported by an open mesh which adds dimensionable stability to the product whilst retaining a high level of conformability. This product has many applications including foam and rubber lamination.

Technical Details

Thickness Adhesive + Scrim 0.06mm

Release Liner Amber glassine 0.080mm

Adhesive Solvent acrylic

Adhesive Strength 600N/m Static Shear 60 hours

Temperature Resistance -20° to +100° C

Release 12N/m UV Light Resistance No Plasticiser Resistance No

Storage

Store in cool conditions in original packaging away from direct sunlight or heat sources

This information and our technical advice, whether verbal, in writing or by way of trials, is given in good faith but without warranty. This also applies where proprietary rights are involved. Our advice does not release you from the obligations to check its validity and to test our products as to their suitability for the intended use. The storage, application and use of our products are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale. The information contained within this data sheet is subject to change without notice.

Page 1 of 1 Issue date: 23.08.21